



XLO-Series

Dehumidifier



Prevent damage from moisture problems

When the relative humidity is above 60% for long periods, the risk of mould, rust, wood rot and condensation increases. With all its adverse consequences, such as damage to floors and furniture, but also e.g. paper, art and antiques. Particularly poorly ventilated and unheated spaces such as basements and garages are vulnerable to moisture problems. With XLO-series dehumidifiers, these problems can be prevented.

XLO dehumidifiers are so-called condensation dryers. The air is sucked into the dehumidifier by a fan over a cold evaporator block. Due to the strong cooling of the air, much of the water vapour contained in it is precipitated. This condensed water is collected in the built-in 11.4-litre reservoir. The cooled air then passes a warm condenser block and is blown back into the room as dry air.

i-EcoDefrost

The i-EcoDefrost technology ensures faster and better defrosting of the cooling element, allowing the appliance to dehumidify faster and more energy-efficiently. When the cooling coils freeze, the compressor switches off, thereby stopping the cooling process. However, the fan continues to run.

This causes room air to flow through the dehumidifier, which melts the ice and the water flows into the reservoir.

De XLO-series dehumidifiers are robust units made for long-term and intensive use. Thanks to the wheels, the dehumidifier is easy to move around. If you do not want to empty the reservoir all the time, it is possible to connect a permanent drain. Of course, the dehumidifiers are also protected against water overflow and freezing.

For optimal operation, it is important to take enough capacity so that the dehumidifier does not have to run continuously. Using the built-in hygostat, the humidity is automatically kept at your desired level.

XLO-series

SPECIFICATIONS PER MODEL

	XLO100	XLO140	XLO190	XLO230
Max. capacity	13,5 l / day	19 l / day	25,5 l / day	41 l / day
Max. space	100 m ²	140 m ²	190 m ²	230 m ²
Max. power	190 W	425 W	550 W	690W
Noise	54-58 dB	55-59 dB	56-60 dB	56-60 dB
i-EcoDefrost	No	Yes	Yes	Yes
Weight	18,5 kg	21,5 kg	24 kg	24 kg

SPECIFICATIONS XLO-SERIES

Main Voltage	230V/50hz	Aut. Hygostat	Yes
Operation	Manual, 2 positions	Permanent drain	optional
Mounting	Standing, mobile	Protection class	IPX1
Dimensions (hxwx d)	527 x 345 x 495 mm	Refrigerant	R290 (not CFC)
Housing	Steel	Warranty	Private 2 years, Business 1 year
Colour	Silver		